


Specifications:
 Current rating:3A AC,DC
 Voltage rating:250V AC,DC
 Contact resistance:15m Ohm min
 Insulation resistance:1000M Ohm min
 Withstanding voltage:600V AC/minute
 Temperature range:-25°C to +85°C
 Material

Insulator:NORYL(UL94V-1)
 How To Order
 2226A-XX

└── No. Of Positions
 └── A:Single Row



CIRCUITS	DIMENTION		CIRCUITS	DIMENTION	
	A	B		A	B
1	2.65		21	53.54	50.80
2	5.28	2.54	22	56.08	53.34
3	7.82	5.08	23	58.62	55.88
4	10.36	7.62	24	61.16	58.42
5	12.90	10.16	25	63.70	60.96
6	15.44	12.70	26	66.24	63.50
7	17.98	15.24	27	68.78	66.04
8	20.52	17.78	28	71.32	68.58
9	23.06	20.32	29	73.86	71.12
10	25.60	22.86	30	76.40	73.66
11	28.14	25.40	31	78.94	76.20
12	30.68	27.94	32	81.48	78.74
13	33.22	30.48	33	84.02	81.28
14	35.76	33.02	34	86.56	83.82
15	38.30	35.56	35	89.10	86.36
16	40.84	38.10	36	91.64	88.90
17	43.38	40.64	37	94.18	91.44
18	45.92	43.18	38	96.72	93.98
19	48.46	45.72	39	99.26	96.52
20	51.00	48.26	40	101.80	99.06

Notes:
 A,B Dimension Tolerance:
 2P~10P ±0.1;
 11P~20P ±0.2;
 21P~30P ±0.3;
 31P~40P ±0.4;
 41P~50P ±0.5

F				DRAWN: Cel King	GENERAL TOLERANCE: .X=±0.20 .XX=±0.15	繼德工業股份有限公司 Neltron Industrial Co., Ltd.	DESCRIPTION: 2.54mm Single Row Housing	SIZE A4
E								
D				CHECKED: Jeremy Liu	UNIT: MM	PART NO: 2226A-XX		
C	31-JAN-2013	ECN-TW1301004	Allen		SCALE: 1:1			
B	24-MAY-2011	ECN-TW110503	Allen	APPROVAL: Mike Wu	SHEET: 1 / 1			
A	26-Apr-2006		Cel king		PROJECTION:			
REV	DATE	FILE	BY					