

DATA SHEET

AR1015 FM Radio

Single Chip Stereo FM Radio Receiver

Preliminary Datasheet

VERSION 0.20 23-Aug-2011

AIROHA
Airoha Technology Corp.

This document is commercially confidential and must NOT be disclosed to third parties without prior consent. The information provided herein is believed to be reliable. But production testing may not include testing of all parameters. AIROHA Technology Corp. reserves the right to change information at any time without notification. ([HTTP://WWW.AIROHA.COM.TW](http://www.airoha.com.tw) TEL:+886-3-6128800 FAX:+886-3-6128833 sales@airoha.com.tw)

This document is commercially confidential and must **NOT** be disclosed to third parties without prior consent.

The information provided herein is believed to be reliable. But production testing may not include testing of all parameters. AIROHA Technology Corp. reserves the right to change information at any time without notification.

Revision History

Version	Change Summary	Date	Author
0.10	Created	13-Jul-2011	Raindrop
0.20	Schematic update	23-Aug-2011	Raindrop

Confidential

INDEX

Revision History.....	3
1 Features.....	5
2 Description.....	5
3 Pin Assignment.....	6
3.1 PIN NAME DESCRIPTION.....	7
4 Block Diagram and Description.....	8
4.1 GENERAL DESCRIPTION.....	8
4.2 RADIO RECEIVER.....	8
4.3 FM SIGNAL PROCESSING UNIT.....	9
4.4 SERIAL 2-WIRE INTERFACE.....	9
5 Electrical Characteristics.....	11
5.1 ABSOLUTE MAXIMUM RATINGS.....	11
5.2 DC ELECTRICAL SPECIFICATIONS.....	11
5.3 AC ELECTRICAL SPECIFICATION.....	12
6 Package Dimension.....	13
7 Schematic.....	15
7.1 CRYSTAL SOLUTION.....	15
7.2 EXTERNAL CLOCK SOLUTION (32.768 KHz).....	16
7.3 EXTERNAL CLOCK SOLUTION (24 MHz).....	17

1 Features

- Worldwide FM band support: 64MHz~108MHz
- Highest integration level with minimized external BOM cost
- Frequency synthesizer with integrated VCO and Automatic Frequency Control (AFC)
- Integrated XO with external reference clock input (32.768KHz, 32KHz, 4.5MHz, 12MHz, 13MHz, 19.2MHz, 24MHz, 26Mhz, 27MHz, 38.4MHz) or external 32.768KHz crystal
- Automatic Gain Control (AGC) on LNA/VGA amplifiers
- Signal strength measurement
- Programmable de-emphasis time constant (50/75us)
- Adaptive noise suppression
- Analog output with volume control and Line-level outputs
- Serial control interface for 2-wire mode
- Embedded Seek tuning function
- Integrated LDO regulators support 2.2V to 3.6 V supply voltage
- Support 32 Ω output load resistance
- MSOP 3x4.9x1mm 10-pin package

2 Description

AR1015 is a highly integrated single chip stereo FM radio receiver for all kinds of applications. AR1015 supports worldwide FM bands from 64MHz to 108MHz. It integrates LNA, Mixer, Oscillator and LDO regulator to minimize the external BOM cost. The built-in FM signal processing unit with noise reduction mechanism provides optimum sound quality. A simple 2-wire interface allows easy control from the host.

3 Pin Assignment




3.1 Pin Name Description

PIN	SIGANL	TYPE	DESCRIPTION
1	DATAIO	Input/Output, Digital	Serial Interface
2	VCC	VCC Supply	Supply Voltage
3	LOUT	Output, Analog	Left Audio Output
4	ROUT	Output, Analog	Right Audio Output
5	GND	GND	Analog Ground
6	VCCCAP	Analog	VCC Capacitor Pin
7	GNDRF	GND	RF Ground
8	RFIN	Input, Analog	RF Input
9	XTAL	Analog	XTAL Input/External REFCLK input
10	CLOCK	Input, Digital Control	Serial Interface

4 Block Diagram and Description

4.1 General Description



AR1015 is a single chip FM radio receiver IC, which supports full 64MHz to 108MHz band. AR1015 integrates on-chip LNA, Mixer, VGA, XO, FM signal processing unit, serial digital I/O interfaces and regulator. The highest integration level minimizes external BOM cost and provides optimum sound quality.

4.2 Radio Receiver

The Radio Receiver part comprises a LNA, a Low-IF mixer and a VGA. The front-end gain of the LNA could be adjusted automatically and thus optimize the received signal-to-noise ratio. The RF signal is then converted to Low-IF band and amplified by the VGA, which is also automatically adjusted. After then the received signal is fed into the FM signal processing unit.

An internal reference oscillator is integrated, so only an external 32.768KHz crystal or a

REFCLK signal is required. (32.768KHz, 32KHz, 4.5MHz, 12MHz, 13MHz, 19.2MHz, 24MHz, 26Mhz, 27MHz, 38.4MHz)

4.3 FM signal processing Unit

The main function of the FM signal processing unit includes FM Demodulation and Stereo Decoding . The received FM signal at VGA output is first demodulated into stereo multiplexed signals (Left+Right and Left–Right) and then decoded into Left and Right signals individually by the stereo decoder. Two time constants (50 μ s or 75 μ s) of de-emphasis are provided and programmable through the serial interface.


The decoded stereo signals are output to the LOUT and ROUT pins. The output volume could be adjusted or mute through the serial interface. The stereo output could be blocked and only mono signal is output under weak signals.

4.4 Serial 2-Wire Interface


Serial 2-wire interfaces are provided to read and write the control registers.

SYMBOL	PARAMETER	MIN	TYP	MAX	UNIT
	CLOCK Frequency	0		400	KHz
T _{S1}	CLOCK Input to DATA N-edge Setup time (START)	600			ns
T _{H1}	CLOCK Input to DATA N-edge Hold time (START)	600			ns
T _{S2}	DATA Input to CLOCK P-edge Setup time	100			ns
T _{H2}	DATA Input to CLOCK N-edge Hold time	0		900	ns
T _{S3}	CLOCK Input to DATA P-edge Setup time (STOP)	600			ns
T _{BUF}	STOP to START time	1300			ns
T _{OF}	DATA Output Fall time	20		250	ns
T _{IR}	DATA Input & CLOCK Rise time	20		300	ns
T _{IF}	DATA Input & CLOCK Fall time	20		300	ns
T _{HIGH}	CLOCK HIGH duration	600			ns
T _{LOW}	CLOCK LOW duration	1300			ns
T _{PS}	Input Filter Pulse Suppression			50	ns

2-Wire Interface Read and Write Timing Parameters



2-Wire Interface Read and Write Procedure



5 Electrical Characteristics

5.1 Absolute Maximum Ratings

AR1015 could be damaged by any stress in excess of the absolute maximum ratings listed below.

ITEM	MIN.	MAX.
Power supply voltage (VCC)	- 0.3V	3.6V
Pin voltage	- 0.3V	HOST_IO_VCC + 0.3V
Maximum power dissipation	-	1W
Operating temperature	- 40°C	+85°C
Storage temperature	- 65°C	+150°C
LNA input level	-	+10 dBm

5.2 DC Electrical Specifications

Recommended operating ambient temperature range $T_A = -20$ to 85°C

Item	Symbol	Test Condition	Min.	Typ.	Max.	Unit
VCC Supply Voltage	VCC		2.2		3.6	V
VCC Supply Current	I_{VCC}	ENABLE=1		15.5		mA
Power Down Current	I_{VCC}	ENABLE=0		7	20	μA
Digital Input Voltage – High Level	V_{IH}		$0.7 \cdot V_{CC}$		$V_{CC} + 0.3$	V
Digital Input Voltage – Low Level	V_{IL}		- 0.3		$0.3 \cdot V_{CC}$	V
Digital Input Current – High Level	I_{IH}	$V_{IN} = V_{CC} = 3.6\text{V}$	-10		10	μA
Digital Input Current – Low Level	I_{IL}	$V_{IN} = 0\text{V}, V_{CC} = 3.6\text{V}$	-10		10	μA
Interface Output Voltage – High Level	V_{OH}	$I_{OUT} = 500\mu\text{A}$	$0.8 \cdot V_{CC}$			V
Interface Output Voltage – Low Level	V_{OL}	$I_{OUT} = - 500\mu\text{A}$			$0.2 \cdot V_{CC}$	V

5.3 AC Electrical Specification


Typical values are tested under VCC=3.3V, Ta=25°C unless otherwise specified

PARAMETER	CONDITION	MIN.	TYP.	MAX.	UNIT
Input Frequency		64		108	MHz
Sensitivity	(S+N)/N=26dB, FD=22.5KHz		1.8	3.5	μVemf
LNA Input Resistance			126		Ω
LNA Input Capacitance			3.6		pF
IIP3			86		dBμV
AM Suppression	m=0.3		70		dB
Adjacent Channel Selectivity (Low side)	-200KHz		38		dB
	+200KHz		55		dB
	-400KHz		>60		dB
	+400KHz		>60		dB
Spurious Response Rejection	In-band		38		dB
Crystal REFCLK Frequency			32.768		KHz
External REFCLK Frequency		32K		38.4M	Hz
REFCLK Frequency Tolerance	25 °C	-20		+20	ppm
	-20 °C ~ +85 °C	-150		+150	ppm
Audio Output Voltage *1,	FD=22.5KHz, at max. vol.	85	95	105	mV _{RMS}
Audio Output L/R Imbalance *1	FD=75KHz	-0.5		0.5	dB
Audio Stereo Separation *1	FD=75KHz including 9% pilot		40		dB
Audio S/N *1	FD=22.5KHz		56		dB
Audio THD *1,	FD=75KHz		0.1		%
De-emphasis Time Constant			75		μs
			50		μs
Audio Common-mode Voltage			0.85		V
Audio Output Load Resistance	Single-end	32			Ω

note *1 : VRF=60dBuV

6 Package Dimension

Package:MSOP-10pin/3x4.9x1mm/0.5 pitch,




SYMBOL	10L MSOP		
	MIN	NOM.	MAX.
A	--	--	1.10
A1	0.00	--	0.15
A2	0.75	0.85	0.95
b	0.17	--	0.33
D	2.90	3.00	3.10
E	4.70	4.90	5.10
E1	2.90	3.00	3.10
R	0.07	--	--
R1	0.07	--	--
L	0.40	0.55	0.70
L1	0.95 REF		
e	0.50 BSC		
ddd	0.08		
ccc	0.10		
N	10		

Notes:

1. ALL DIMENSIONS ARE IN MILLIMETERS (ANGLES IN DEGREES).
2. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M-1994.
3. DIMENSION 'D' DOES NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS.
4. DIMENSION 'E1' DOES NOT INCLUDE INTERNAL FLASH OR PROTRUSION.
5. DIMENSION 'b' DOES NOT INCLUDE DAMBAR PROTRUSION.
6. FOOT LENGTH 'L' IS MEASURED AT GAGE PLANE, AT 0.254 ABOVE THE SEATING PLANE.


7 Schematic

7.1 Crystal solution




- Note1: The pull-high resistors (R2&R1) must be added on 2-wire CLOCK(pin10) & DATAIO(pin1) respectively. 20K ohm resistors are recommended .
- Note2: C4 and C5 must be reserved for fine tune performance. The two capacitors should be close to Host Controller.
- Note3: C2(1uF) must be as close to VCC(pin2) as possible.
- Note4: C3 must be reserved on PCB and it should be close to pin6.
- Note5: Y1 should be as close to pin9 as possible .

7.2 External Clock solution (32.768 KHz)



- Note1: The pull-high resistors (R2&R1) must be added on 2-wire CLOCK(pin10) & DATAIO(pin1) respectively. 20K ohm resistors are recommended .
- Note2: C4 and C5 must be reserved for fine tune performance. The two capacitors should be close to Host Controller.
- Note3: C2(1uF) must be as close to VCC(pin2) as possible.
- Note4: C3 must be reserved on PCB and it should be close to pin6.

7.3 External Clock solution (24 MHz)



- Note1: The pull-high resistors (R2&R1) must be added on 2-wire CLOCK(pin10) & DATAIO(pin1) respectively. 20K ohm resistors are recommended.
- Note2: C4 and C5 must be reserved for fine tune performance. The two capacitors should be close to Host Controller.
- Note3: C2(1uF) must be as close to VCC(pin2) as possible.
- Note4: C3 must be reserved on PCB and it should be close to pin6.
- Note5: The external clock swing to AR1015 pin9 should be 0.9-0.8Vpp(C6 and C7 should be fine tuned) for the best performance. C6 and C7 should be close to Host Controller, too.